




FITTING INSTRUCTIONS FOR TH0007
TRANSPORT HOOKS FOR HONDA CBR500R '16-



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW.
DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike.

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY).



LEGEND

- ITEM 1 = TRANSPORT HOOK LEFT (SMW0064) (x1).
 ITEM 2 = TRANSPORT HOOK RIGHT (SMW0065) (x1).
 ITEM 3 = M8 x 30mm LONG COUNTERSUNK BOLTS (x2).
 ITEM 4 = M8 x 25mm LONG COUNTERSUNK BOLTS (x2).



Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

TOOLS REQUIRED

- Socket set to include 5 & 6mm socket and wrench.

GENERAL TORQUE SETTINGS

M4 BOLT = 8Nm
 M5 BOLT = 12Nm
 M6 BOLT = 15Nm
 M8 BOLT = 20Nm
 M10 BOLT = 40Nm

FITTING INSTRUCTIONS

- Remove the OEM pillion footrests on both sides of the bike.
- Offer the left side R&G transport hook (item 1) into position on the bike and tighten into the thread on the subframe using the two M8 x 25mm long countersunk bolts (item 4), as shown above.
- On the right side, the transport hook can only be fitted when using the R&G Exhaust Hanger, available separately.
- With the R&G Exhaust Hanger fitted, remove the two top bolts that mount the hanger to the subframe.
- Offer the right side R&G transport hook (item 2) into position on the bike and tighten into the thread on the subframe using the two M8 x 30mm long countersunk bolts (item 4), as shown above.
- Ensure the part is correctly fitted before tightening all bolts to the recommended torque values.
-
- *Please ensure that when strapping the motorcycle down the ratchet straps do not come into contact with any part of the motorcycle, as the strap is likely to rub during transit and may cause damage.*

ISSUE 1 04/08/2016 (AR)

Digital copies of these instructions are available to download from www.rg-racing.com

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com




NOTICE DE MONTAGE TH0007
ATTACHES DE TRANSPORT POUR HONDA CBR500R '16-



Le kit contient les articles exposés ci-dessous, vérifier que toutes les pièces soient présentes avant de procéder au montage.

La façon dont le kit est emballé ne correspond pas forcément à la façon de monter les pièces sur la moto.

LES PARTIES PRESENTEES PEUVENT ETRE UNIQUEMENT REPRESENTATIVES (POUR LA CLARTE DES INSTRUCTIONS UNIQUEMENT).





LEGENDE

ARTICLE 1 = ATTACHE DE TRANSPORT COTE GAUCHE (SMW0064) (x1).

ARTICLE 2 = ATTACHE DE TRANSPORT COTE DROIT (SMW0065) (x1).

ARTICLE 3 = M8 x 30mm BOULONS **A TETE PLATE** (x2).

ARTICLE 4 = M8 x 25mm BOULONS **A TETE PLATE** (x2).

Notez que si les kits sont emballés avec des rondelles en caoutchouc servant à tenir les composants, *ces rondelles doivent être jetées!*

OUTILS REQUIS

- Clés Allen 5 & 6mm.

COUPLES DE SERRAGE RECOMMANDÉS

M4 BOULON = 8Nm

M5 BOULON = 12Nm

M6 BOULON = 15Nm

M8 BOULON = 20Nm

M10 BOULON = 40Nm

NOTICE DE MONTAGE

- Enlever les repose pieds d'origine des 2 cotés de la moto.
- Monter l'attache de transport R&G du côté gauche (article 1) en position sur la moto puis serrer dans le filetage du sous cadre à l'aide de 2 boulons M8 x 25mm (article 4), comme indiqué ci-dessus.
- Du côté droit, l'attache de transport peut seulement être installée en utilisant le support d'échappement R&G, disponible séparément.
- Une fois le support d'échappement R&G installé, enlever les 2 boulons supérieurs qui fixent le support au sous cadre.
- Monter l'attache de transport R&G du côté droit (article 2) en position sur la moto puis serrer dans le filetage du sous cadre à l'aide de 2 boulons **à tête plate** M8 x 30mm (article 4), voir ci-dessus.
- Veiller à ce que toutes les parties soient correctement montées avant de serrer tous les boulons selon les couples de serrage recommandés.

Veiller à ce que lorsque vous sanglez la moto, le cliquet ne puisse pas toucher quelque partie de la moto.

ISSUE 1 04/08/2016 (AR)

Notice de montage disponible sur www.rg-racing.com

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com

**R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.