

# FITTING INSTRUCTIONS FOR CP0039 CRASH PROTECTORS TRIUMPH TT600

## Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away*!

### Near side (left side as you sit on bike)

- Remove upper fairing
- Remove *engine to frame* M10 diameter bolt.
- Insert one of the supplied M10 bolts into the bolt hole and paint the exposed end.
- Offer the fairing back into position so that the paint marks the position inside the fairing.
- Using a 25mm tank cutter (hole saw), drill through the fairing with the pilot drill using the mark made by the paint to find the centre. Replace the fairing and ensure that the pilot hole is in the correct position. Remove the fairing and support it. Drill through carefully from the outside with the tank cutter.
- Replace the fairing
- Slide one of the washers onto the bolt
- Next, slide the longer crash protector onto the bolt
- Finally, slide the larger spacer onto the bolt
- . Insert assembly through new fairing hole, ensuring that the spacer fits neatly into the recess in the frame
- Tighten assembly with a 17mm socket, ensuring that you do not over-tighten (this will cause frame damage). Tighten bolt until you feel some compression from inside the protector. Turn a little more so that you feel the compression increase slightly. Then apply a quarter turn. Do not overtighten as damage can occur to the bike. Do not exceed 40nm of torque.

Repeat for offside, except using smaller spacer and smaller crash protector.

### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

## **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.