


<u>Fitting Instructions for RAD0073BK/TI</u> Radiator and Oil Cooler Guard - Triumph Tiger 1050 '07-



In This Kit There Should Be
1x Radiator Guard.
2x 100mm Lengths of Foam.

- To fit the radiator guard to the bike cut the foam strips provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove the infill panel situated between the radiator and oil cooler.
- Remove the two original mounting bolts located at the top of the radiator and also remove the three mounting bolts located at the bottom on the oil cooler. Fit the radiator guard into position and fix in place using the original mounting bolts previously removed. Please note you will not be able to refit the plastic infill panel.

ISSUE 2 25/08/2011 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



FRANCE

<u>Instructions de montage de la protection de radiateur et radiateur huile</u> RAD0073BK/TI

Triumph Tiger 1050 '07-

Ce kit contient 1x Protection de radiateur (RAD0073BK-TI) 2x bandes de mousse 100 mm

- Pour fixer la protection de radiateur sur la moto, vous devez couper des morceaux de mousse de 10 mm et les coller sur l'arrière de l'armature de la protection (de manière à ce qu'ils soient positionnés entre le radiateur et la protection R&G).
- Enlever le cache / protection plastique situé entre le radiateur et le radiateur d'huile
- Dévisser et enlever les deux vis de fixation du radiateur (fixations hautes)
- Dévisser et enlever la vis de fixation du radiateur d'huile -3 vis situées à l'arrière
- Placer la protection sur la moto et utilisez les vis de fixation d'origine pour maintenir la protection sur la moto.
- Attention, le cache en plastique d'origine ne pourra pas être réutilisé.

•

